

Product information

Art no	390111	390208	390112	390210	390113	390212	390114	390214	398163	398164	398204	398205	398234	398235
Item	TCD 10W/827	TCD 10W/830	TCD 13W/827	TCD 13W/830	TCD 18W/827	TCD 18W/830	TCD 26W/827	TCD 26W/830	TCD/E 13W/827	TCD/E 13W/830	TCD/E 18W/827	TCD/E 18W/830	TCD 26W/827	TCD/E 26W/830
Nominal wattage (W)	10	10	13	13	18	18	26	26	13	13	18	18	26	26
Rated lifetime (h)	10000	10000	10000	10000	10000	10000	10000	10000	13000	13000	13000	13000	13000	13000
Rated lamp survival at 2000h (%)	99	99	99	99	99	99	99	99	99	99	99	99	99	99
Rated lamp survival at 4000h (%)	97	97	97	97	97	97	97	97	98	98	98	98	98	98
Rated lamp survival at 6000h (%)	93	93	93	93	93	93	93	93	94	94	94	94	94	94
Rated lamp survival at 8000h (%)	85	85	85	85	85	85	85	85	88	88	88	88	88	88
Mercury content (mg)	2,5	2,5	2,5	2,5	2,5	2,5	2,5	2,5	2,5	2,5	2,5	2,5	2,5	2,5
Nominal luminous flux (lm)	600	600	900	900	1200	1200	1800	1800	900	900	1200	1200	1800	1800
Lumen maintenance 2000h (%)	91	91	91	91	91	91	91	91	91	91	91	91	91	91
Lumen maintenance 4000h (%)	87	87	87	87	87	87	87	87	87	87	87	87	87	87
Lumen maintenance 6000h (%)	84	84	84	84	84	84	84	84	84	84	84	84	84	84
Lumen maintenance 8000h (%)	80	80	80	80	80	80	80	80	80	80	80	80	80	80
Rated lamp efficacy (lm/W)	60	60	69	69	67	67	69	69	69	69	67	67	69	69
Color temperature (K)	2700	3000	2700	3000	2700	3000	2700	3000	2700	3000	2700	3000	2700	3000
Ra-index	80-89	80-89	80-89	80-89	80-89	80-89	80-89	80-89	80-89	80-89	80-89	80-89	80-89	80-89
Energy class	B	B	A	A	B	B	B	B	A	A	B	B	B	B
Max lamp length (mm)	108	108	138	138	153	153	173	173	131	131	146	146	165	165
Length excl base pins (mm)														
Tube diameter (mm)	12	12	12	12	12	12	12	12	12	12	12	12	12	12
Base	G24-d1	G24-d1	G24d-1	G24d-1	G24d-2	G24d-2	G24d-3	G24d-3	G24q-1	G24q-1	G24q-2	G24q-2	G24q-3	G24q-3